

		<b>4A-GE</b>	
CC (cu. in)		1587 (96.8)	
 *Using a belt tension gauge/kg		6-7 (0.24-0.28) *30-45	
		8-9.5 (0.31-0.37) *35-45	
		—————	
 A	<b>ND</b>	PQ16R (w/ Catalyst) Q20R-U11 (Others)	
	<b>NGK</b>	BCPR5EP11 (w/ Catalyst) BCPR6EY11 (Others)	
	A	1.1 (0.043) mm (in)	
		KΩ	
 A	B	—————	
	B	—————	
		10°	
 BTDC		0.15-0.25 (0.006-0.010)	
		0.20-0.30 (0.008-0.012)	
		800 rpm	
		0-0.5 (w/ Catalyst) 1.0-2.0 (Others) CO%	

		12.6 (Europe (w/ Catalyst)) 17.9 (General)	
		12.7 (Europe (w/o Catalyst)) 18.1	
		10.0 (142)	
		1.0 (14)	
		400 (15.75)	
		0.3 (4.3)	
		2.5-5.0 (36-71)	
		300 (22) 90° 90°	
 A	B	280 (20)	
	C	250 (18)	

		<b>4A-GE</b>	
		3.1 (2.7)	
		3.4 (3.0)	
		Europe API SE, SF General API SC, SD, SE, SF liter (Imp. qts)	
		12.4 (10.9) liter (Imp. qts)	

<b>A</b>	153-163 (6.02-6.42)	168-178 (6.61-7.01)	
<b>B</b>	5-15 (0.20-0.59)		
<b>mm (in)</b>	SAE J1703, FMVSS No.116 DOT3		

<b>A</b>	154-164 (6.06-6.46)	160-170 (6.30-6.69)	
<b>B</b>	3-6 (0.12-0.24)		
<b>C</b>	87 (3.43)	80 (3.15)	
<b>mm (in)</b>	SAE J1703, FMVSS No.116 DOT3		

	20 kg (44 lb)		
		5-8	

<b>A</b>	1.0 (0.039)		
<b>B</b>	21.0 (0.827)	9.0 (0.354)	
<b>mm (in)</b>			

<b>mm (in)</b>			

<b>mm (in)</b>			

		AW
	mm (in)	0 (0)
	kg (lb)	—
	kg-cm (ft-lb)	1050 (76)

		AW
	liter (imp. qts)	2.6 (2.3)
	API GL-4,5 SAE 75W-90, 80W-90	

	liter (imp. qts)	—
--	------------------	---

	liter (imp. qts)	—
--	------------------	---

		AW
	mm (in)	30 (1.18)

<b>A</b>	0°15' ± 30'	-55° ± 30'
<b>B</b>	12° ± 30'	—
<b>C</b>	5°05' ± 30'	—
<b>D</b>	36°30'	—
<b>E</b>	21°	—

	mm (in)	1 ± 1 (0.04 ± 0.04)	5 ± 1 (0.20 ± 0.04)
--	---------	------------------------	------------------------

	mm (in)	3.0 (0.118)	—
--	---------	----------------	---

185/60 R14 82H	1.8 (26) *2.0 (29)	2.0 (29) *2.2 (32)	2.4 (35)	2.6 (38)
<b>kg/cm² (psi)</b>	*160km/h			