






















		3S-GE	3S-FE
		1998 (121.8)	
CC (cu. in.)		10-15 (0.39-0.59)	
	mm (in.)	7-10 (0.28-0.39)	
	ND	Europe w/ Catalyst, Australia PK20R8 Europe w/o Catalyst K20R-U	K20R-U11
	NGK	w/ Catalyst BKR6EP8 w/o Catalyst BKR6EYA	BKR6EYA-11
	A	0.8 (0.031)	1.1 (0.043)
	mm (in.)		
	K Ω	25	
	A	—	
	B	—	
	mm (in.)		
	BTDC	(Check Connector TE-E connected)	10°
		0.15-0.25 (0.008-0.010)	0.19-0.29 (0.0075-0.0114)
		0.20-0.30 (0.008-0.012)	0.28-0.38 (0.0110-0.0150)
	mm (in.)		
	rpm	800	700
	CO%	w/ Catalyst 0.5 w/o Catalyst 0.5-1.5 (Check Connector TE-E connected)	0.5

	kg/cm ² (psi, kPa)	13.5 (192, 1324)	13.0 (186, 1275)
	mmHg (in. Hg, kPa)	11.0 (156, 1079)	10.0 (142, 981)
	3,000 rpm	1.0 (14, 98)	
	kg/cm ² (psi, kPa)	450 (17.72, 60.0)	
	kg-cm (ft-lb, N-m)	0.3 (4.3, 29)	
	A	2.5-5.0 (36-71, 245-490)	
	B	500 (36, 50)	
	C	195 (14, 19)	
		500 (36, 50)	

		3S-GE	3S-FE
	liter (US qts, Imp. qts)	3.6 (3.8, 3.2)	3.8 (4.0, 3.3)
		3.9 (4.1, 3.4)	4.2 (4.4, 3.7)
		API SE, SF	
	liter (US qts, Imp. qts)	13.6 (14.4, 12.0)	13.0 (13.7, 11.4)
		—	13.0 (13.7, 11.4)

A	184 - 194 (7.24 - 7.64)	192 - 202 (7.56 - 7.95)	
B	5 - 15 (0.20 - 0.59)		
C	25 (0.98)		
SAE J1703, FMVSS No. 116 DOT3			

A	177 - 187 (6.97 - 7.36)	185 - 195 (7.28 - 7.68)	
B	3 - 5 (0.12 - 0.20)		
C	117 (4.61)	120 (4.72)	
SAE J1703, FMVSS No. 116 DOT3			

	20 kg (44.1 lb, 196 N)		
	5 - 8		

A	1.0 (0.039)		
B	Europe 23.0 (0.906)	15.0 (0.591)	
	Australia 24.0 (0.945)		

	—		
--	---	--	--

	—		
--	---	--	--

	SW		
	0		
	—		
	1050 (76, 103)		

	SW		
	2.6 (2.7, 2.3)		
	ATF DEXRON® II		
	3.4 (3.6, 3.0)		
	ATF DEXRON® II		
	—		

	SW		
	—		

	SW		
	30 (1.18)		

A	-50° ± 30'	-1°25' ± 30'	
B	13°30' ± 30'	—	
C	2°45' ± 30'	—	
D	37.5° ± 1°30'	—	
E	22°	—	
	1 ± 1 (0.04 ± 0.04)	5 ± 1 (0.20 ± 0.04)	
	3.0 (0.118)	—	

	160 km/h = 100 mph km/h		
Europe	195/60R14 85V	205/60R14 88V	
U.K.	2.0 (29, 200)	2.3 (33, 230)	
Austria	160 160	1.8 (26, 180) 2.2 (32, 220)	2.2 (32, 220) 2.7 (39, 270)
Others	160 160	1.8 (26, 180) 2.0 (29, 200)	2.2 (32, 220) 2.4 (35, 240)
Australia	195/60R14 85V	205/60R14 88V	
	140 140	2.0 (29, 200) 2.8 (41, 280)	2.2 (32, 220) 3.0 (44, 300)