



























		3S-GE	3S-FE
		1998 (721.9)	
CC (cu in.)		1998 (721.9)	
		10-15 (0.39-0.59) ※ 20-45	13-17 (0.51-0.67) ※ 20-45
mm (in.)	kg	7-10 (0.28-0.39) ※ 25-40	
	ND	Europe w/ Catalyst, Australia PK20R8 Europe w/o Catalyst K20R-U	K20R-U11
	NGK	w/ Catalyst BKR6EP8 w/o Catalyst BKR6EYA	BKR6EYA-11
	A	0.8 (0.031)	1.1 (0.043)
mm (in.)			
	kΩ	25	
	A	—	
	B	—	
mm (in.)			
	BTDC	10° (Check Connector TE-E connected)	
		0.15-0.25 (0.006-0.010)	0.19-0.29 (0.0075-0.0114)
		0.20-0.30 (0.008-0.012)	0.28-0.38 (0.0110-0.0150)
mm (in.)			
	rpm	850 (w/ Daytime Running Light System) 800 (Others)	700
	CO%	w/ Catalyst ↓ 0.5 w/o Catalyst 0.5-1.5 (Check Connector TE-E connected)	↓ 0.5

		13.5 (192, 1324)	13.0 (185, 1276)
		11.0 (156, 1079)	10.0 (142, 981)
kg/cm ² (psi, kPa)		1.0 (14, 98)	
		450 (17.72, 60.0)	
mmHg (in. Hg, kPa)			
		0.3 (4.3, 29)	
kg/cm ² (psi, kPa)		2.5-5.0 (36-71, 245-490)	
3,000 rpm			
	A	500 (36, 49)	90°
	B	195 (14, 19)	
	C	530 (38, 52)	
kg-cm (ft-lb, N-m)			

		3S-GE	3S-FE
		3.6 (3.8, 3.2)	3.8 (4.0, 3.3)
		3.9 (4.1, 3.4)	4.2 (4.4, 3.7)
liter (US qts, Imp. qts)		API SE, SF or better	
API SE, SF or better		API SE, SF, SG or better	
		13.6 (14.4, 12.0)	13.0 (13.7, 11.4)
		—	13.0 (13.7, 11.4)
liter (US qts, Imp. qts)			